



CUNIMET[®]
ALLOYS PVT. LTD.

CUNIMET ALLOYS PVT. LTD.
Plot No.17A Parshwa Industries Park ,
Behind New Gidc, Dehari
Umbergaon 396170
www.cunimet.com,
sales@cunimet.com

CROSS

SOCKET WELD


Specification: NAVSEA DWG 803-6397430

Pressure Rating: 400 PSIG (WOG)

**Intended for use with Class 200 or 700
Copper Nickel Tube IAW MIL-T-16420**

SERVICE RATING TABLE

Nominal Pipe Size (INCHES)	Maximum Working Pressure (LB/IN ²)	Maximum Temperature (°F)	Maximum Working Pressure (LB/IN ²)	Maximum Temperature (°F)
1/4 through 6	200	425	400	150
Above 6	150	425	250	150



**70/30 CUNI
(ALLOY C715/C964)**



**90/10 CUNI
(ALLOY C706/C962)**

AVAILABLE ALLOYS: CUNI 90/10 & CUNI 70/30

NOMINAL PIPE SIZE	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
P/N (90/10)	CR9SW040	CR9SW060	CR9SW100	CR9SW150	CR9SW200	CR9SW250	CR9SW300	CR9SW400	CR9SW450	CR9SW500	CR9SW550	CR9SW600
P/N (70/30)	CR7SW040	CR7SW060	CR7SW100	CR7SW150	CR7SW200	CR7SW250	CR7SW300	CR7SW400	CR7SW450	CR7SW500	CR7SW550	CR7SW600
A	0.71	0.82	1.01	1.18	1.43	1.69	1.84	2.12	2.7	3.08	3.42	3.79
B	0.945	1.096	1.275	1.503	1.78	2.129	2.387	2.908	3.408	4.041	4.541	5.097
C	.545 (+/- .030)	.680 (+/- .030)	.845 (+/- .030)	1.055 (+/- .030)	1.320 (+/- .030)	1.665 (+/- .030)	1.905 (+/- .030)	2.380 (+/- .046)	2.880 (+/- .051)	3.505 (+/- .055)	4.005 (+/- .055)	4.505 (+/- .060)
D	25/94	5/16	3/8	13/32	7/16	1/2	5/8	23/35	25/32	77/93	7/8	29/32

NOTES: Fittings may be ordered with reduced ends and/or female threads.



CUNIMET[®]
ALLOYS PVT. LTD.